

TITLE OF THE INVENTION

[0001] Improvements in Display Signs and Ornaments for Holiday Seasons

5 FIELD OF THE INVENTION

[0002] This invention relates to an improvement and simplification in ornaments, for example Christmas tree lights, or any ornaments which might be used during holiday seasons. In one embodiment the ornaments are strung together as Christmas lights for decorating homes and trees or the like. In another embodiment the edge lighting may be used for displaying signs or designs.

BACKGROUND OF THE INVENTION

15 [0003] It is heretofore well known to utilize Christmas lights to decorate the interior or exterior of one's home during the holiday seasons. Ornaments for trees are also well known. There are some definite problems which exist with present Christmas ornaments. The actual lighting elements or bulbs may be very unreliable. Therefore, from season to season one can never be sure of the operation of the ornaments.

20 Many lights are strung together in a series circuit and therefore require by nature that each and every bulb be installight source and preferred LED and lit. When a bulb is burnt out it may be necessary for the user to complete a continuity check on each bulb to determine which bulb is in fact burnt out. This is a very time-consuming and frustrating process. In fact known Christmas tree lights are so

25 unreliable it is frequently the case that newly purchased strings of lights will not operate. Of course, the greater frustration comes into play when lights are strung about the perimeter of a home adjacent the roof and the trouble shooting must be done on a ladder.

009900326-112301  
TOTAL: 92E06660

Sub  
air

[0004] It is also well known to provide lighted display signs for advertising purposes. These signs may be lit by conventional methods.

[0005] It is not new to form ornaments from clear or coloured materials with a lighting element inserted in the interior thereof. United States Patent No. 1,410,336 includes a star-shaped ornament for a Christmas tree within which an electric light bulb is placed. However, this ornament is manufactured by a distinct number of elements and does not include a single body or piece of material of predetermined shape and thickness within which an opening is provided. This is also the case with United States Patent No. 2,132,297 which describes a compound structure including a chime utilized as for example in a decorative head piece.

[0006] United States Patent No. 19,859 (Reissued), originally United States Patent No. 1,977,126, describes an ornamental device which is illuminated and utilized in lighting Christmas trees and, holiday decorations. The ornaments are simple, light weight and compact. An envelope is provided with a number of openings wherein lighting elements 5 are inserted. A socket 3 is provided on the bottom of the envelope in order for the entire assembly to engage the electrical connector for the array of lighting. It is stated within the patent that the source of illumination may include other electrical devices such as neon tubes.

[0007] United States Patent No. 4,654,766, issued March 31, 1987, describes a bulb seat in a string of bulbs. As best seen in Figures 1, 2 and 3, the invention describes ornamental or decorative bulbs or strings of bulbs wherein the bulbs may be made smaller. Further, the bulb seat structure is manufactured from transparent material of various colours and includes an opening to receive a bulb therein. The unit is assembled source and preferred LED by inserting the bulb into the opening and bending the conductors into the grooves provided in the perimeter of the ornament. These conductors are then connected to a twisted pair of wires. It is suggested that

the outer shape of the bulb may be of any decorative form, whether as a stand-alone bulb or a string of bulbs. The patent at line 62 of column 2 states that the bulb may be replaced with a light-emitting diode.

5 [0008] United States Patent No. 4,675,575 describes the use of Christmas tree strings including various AC and DC control circuits for driving the light-emitting diodes provided therewith for providing alternating effects between the various colours of the bulbs. The claims define a miniature light bulb for strings of Christmas tree lights including a light-emitting diode, an envelope surrounding at least a portion of  
10 the light-emitting diode, and light conducting spheres contained within the envelope for dispersing and diffusing the light.

15 [0009] United States Patent No. 4,870,325 teaches a lighting display using LIGHT SOURCE AND PREFERRED LEDs which are powered by a particular circuit as described in the patent to enable flashing or oscillating. There is no particular discussion in this reference as to the structure of the lighting elements. This reference discusses LIGHT SOURCE AND PREFERRED LEDs and their use in lighting. This patent sets out at columns 1 and 2 many of the background problems with incandescent lighting including the power consumption of the well-known  
20 Christmas lighting systems. The patent therefore teaches a lighting display device including a string of LIGHT SOURCE AND PREFERRED LEDs connected in parallel, at least one of the LIGHT SOURCE AND PREFERRED LEDs being bi-colour diodes included in an involved pulsing circuitry and switching mechanism which gate the LIGHT SOURCE AND PREFERRED LEDs to on and off positions.

25

[0010] United States Patent No. 4,931,227 describes a transparent body having openings therein as seen in Figures 5, 6, 8 and 9 wherein a matrix of polymethylmethacrylate is utilized for signs incorporating edge-lighting technology. This particular patent improves edge lighting by utilizing light-reflection material

11990325-112301

for obtaining a three-dimensional effect. The material has a number of openings or holes extending therethrough formed by placing threads in pre-determined positions while molding the sign, display sheet, or the like, and then pulling the threads through leaving the openings within the material. The threads may be  
5 alternatively left in the material when formed having no particularly pre-defined route left to the designer. For the light to provide the most desirable reflection pattern, round openings are recommended. Alternatively, the holes may be coloured using various pigments and dies during the forming process. As described in Example 2 at column 6, line 24, the ornament may be a mobile which is edge-lit.  
10 One example is seen in Figures 8 and 9 wherein the edge lighting is produced by a fluorescent tube to obtain various effects at wave-like openings 2 and 3.

[0011] United States Patent No. 4,965,701 describes the use of strings of spaced bulbs contained within translucent spheres which may also have varying shapes including  
15 stars, bells, pyramids, cubes and the like as best seen in Figure 6. The ornament is constructed by two interfitting halves which contain therebetween the bulbs. Each of the illumination members is translucent to enhance the illumination from an alternative fiber-optic cable which extends from an illumination member 27.

[0012] United States Patent No. 4,213,407 teaches a light string for use with a small Christmas tree. The light string is seen in Figures 2 and 4, and includes a plurality of  
20 light-emitting elements which may be light-emitting diodes inside a transparent or translucent cover 35. The cover is shaped to give the appearance of a miniature Christmas-tree bulb in this description. The unit may be powered from a  
25 transformer or batteries which are the preferred source of power.

[0013] United States Patent No. 5,315,492 describes a window display ornament including LIGHT SOURCE AND PREFERRED LEDs as best seen in Figure 5. ✓  
Similarly, United States Patent No. 5,239,450 teaches the use of LIGHT SOURCE

TOEET 9220660

no such  
figs. or element 35

Sub  
A31

AND PREFERRED LEDs for use in buttons with a pre-determined message provided on a flat disk of material.

5 [0014] United States Patent No. 5,249,109 teaches optical fibers used as ornaments in combination with an end lighting element on the bundles thereof.

10 [0015] United States Patent No. 5,495,147 teaches the use of a string of LIGHT SOURCE AND PREFERRED LEDs connected in parallel utilized for decoration and the like including a regulated power supply to provide constant current at a constant voltage as received from an AC line including a step-down transformer to step down the voltage in the range of between 3 and 5 volts AC, a rectifier for rectifying that voltage, a voltage regulator coupled to the output of the transformer and a zener diode coupled to the output of the voltage regulator for limiting the voltage fed into the voltage regulator from the rectifier.

20 [0016] Many of the devices described above especially since they include LIGHT SOURCE AND PREFERRED LED's provide a pin point light, that is to say a very sharp glaring point of light for Christmas ornaments and decorations. It would therefore be desirable to scatter the light from an LIGHT SOURCE AND PREFERRED LED in a pleasing manner through some of the surface area of the ornament being observed.

25 [0017] Nowhere within the prior art to the best of applicant's knowledge is there found; an ornament for holiday seasons; a sign, such as an emergency sign, or a design, such as a company logo; which may be lit by a reliable light source such as light emitting diode by scattering the light produced at much reduced power consumption and substantially reduced operating temperature. It is therefore desirable to provide an ornament/design/sign, in one embodiment

suitable for decorating during a holiday season, which would enhance the lighting effectiveness thereof when compared to of an LIGHT SOURCE AND PREFERRED LED on its own.

5 [0018] It is therefore a primary object of the invention to provide a suitable sign, ornament or design which complements the use of a lighting element to provide much improved pre-selected dispersion of light throughout the sign, design or ornament.

10 [0019] It is a further object of this invention to provide an ornament/sign/design which is easy to manufacture and simple to install and maintain .

[0020] It is yet a further object of this invention to provide a sign, ornament or design which is rugged and reliable with an extended life expectancy.

15 [0021] Further and other objects of the invention will become apparent to those skillight source and preferred LED in the art when considering the following summary of the invention and the more detailight source and preferred LED description of the preferred embodiments illustrated herein.

20 SUMMARY OF THE INVENTION

25 [0022] According to a primary aspect of the invention there is provided an ornament/design or sign, in one embodiment for decorative purposes, for example Christmas tree ornaments or the like, said ornament/design or sign comprising a solid matrix of material providing a body preferably having a top, bottom and plurality of sides, and having a predetermined shape, preferably formed proximate the top thereof and extending toward the bottom thereof, said body having at least one light scattering translucent surface, groove and/or ridge formed therein, and

preferably when the body is providing an ornament, extending about at least some of the perimeter of the body and in one embodiment substantially the entire perimeter of the body, said surface, grooves , ridges or characteristics providing a design, shape, image, letter or character preferably which represents the holiday season, for example a candle, an image of Santa Claus, a crucifix, a heart or the like, all formed by forming and preferably etching the surface, grooves , ridges or characteristics into the matrix of the body of the ornament/design or sign, said body having disposed therein and preferably proximate at least one side thereof an opening having contained therein in use at least one light source, and preferably at least one light emitting diode, which may be glued or molded in place within the opening, or alternatively loosely fit within the opening, said at least one light source including electrical leads extending to an electrical conductor or alternatively to a printed circuit board for the powering thereof; said body in preferred embodiments being manufactured from various materials such as polymethylmethacrylate, acrylic, resins, Lexan® or the like, preferably materials which appear transparent are utilized; the material being of any suitable colour for the holiday season such as amber, red, green, blue, clear, purple, yellow, orange or any shades or combinations thereof; in one embodiment the etching of the body of the ornament/design or sign may further comprise a second etched surface, groove or ridge within the perimeter of the first etched surface groove or ridge, said LIGHT SOURCE AND PREFERRED LED being positioned so as to light the ornament, said light exiting the LIGHT SOURCE AND PREFERRED LED and being dispersed by said light scattering translucent at least one etched surface, groove or ridge so as to create a dispersion of the light which would remain undispersed had the etched surface, grooves , ridges or characteristics not been provided.

[0023] According to yet another aspect of the invention there is provided a display sign comprising a body of solid material for example, methylmethacrylate, acrylic, resin, Lexan®, or the like, preferably said body being transparent and having sides,

5

15

20

25



5

20

25

- (1)

5

10

15

20

25

Sub  
tail

displayed to the public so as to obviate the need for neon signs, house numbering, flares, letters or the like. As described above, the sign may be substantially rectangular in shape and may be contained between two display rails and which may alternatively contain a LIGHT SOURCE AND PREFERRED LED array which  
5 will be disposed within or adjacent to the edge of the display sign so as to provide incident light on the etched surfaces from the edge of the sign.

[0028] In another embodiment the apparatus or method is utilized to manufacture ornaments, for example for Christmas, Halloween or Valentine's Day in many  
10 suitable shapes such as in a shape of hearts, Christmas trees, pine cones, pineapples or the like of many different and combinations of colours and variations thereto which are adapted to be connected with a power supply in a modular fashion for example via plug connectors or the like which allows for simple changing of each ornament, for example the Christmas tree ornaments and their positions in an array.

15 [0029] According to yet another aspect of the invention there is provided an ornament comprising a matrix of clear transparent material such as methylmethacrylate, Lexan®, acrylic or the like, said ornament when suitably oriented having a top and bottom or alternatively being of a predetermined shape,  
20 for example spherical, in one embodiment, preferably said top and bottom of said ornament and at least said top being formed into the desired shape of the ornament such as a Christmas tree, a circle, a piece of fruit, a Santa Claus, or the like and having a predetermined perimeter, preferably said predetermined perimeter being disposed proximate an outer edge of said top and said bottom having therebetween  
25 disposed at least one side, said ornament and preferably said at least one side, having disposed therein at least one opening, said at least one opening for having installed light source and preferred LED therein a light source such as a light-emitting diode or the like, preferably the top and in some embodiments the bottom of the ornament substantially duplicating the shape of the ornament, said ornament

T03230660

Sub  
A12


having an etched or otherwise formed light scattering surface, alphanumeric character(s), design(s), or pleasing shape(s) therein, for example if the ornament were shaped as a leaf the design may include the veins of the leaf, if the design were in the shape of the figure of Santa Claus or the head of Santa Claus a likeness would be contained on the top therein, formed and preferably etched into the matrix enhancing the face or figure of Santa Claus, wherein said etching may further comprise at least one compatibly shaped etched design formed by providing in one embodiment at least one groove or ridge portion, or at least one etched surface, extending in predetermined directions to provide said etched design, wherein the material adjacent the at least one surface, groove or channel or the like is substantially translucent or non-transparent so as to substantially disperse any incident light thereon from the light source in use, the light striking said at least one etched surface, groove, design or the like causing light to disperse and/or scatter from said design to a much greater extent than light passing through a matrix of transparent material, said dispersion or scattering of the light thereby creating a pleasing and more effective ornament.


[0030] In a preferred embodiment the ornament may be of any colour such as amber, red, blue, green, turquoise, orange, purple, or the like, or combinations thereof, and the desired etching being an off shade of said ornament colour. In another embodiment said ornaments include electrical connections which are connected to a conducting lead such as a pair of wires wherein said pairs of wires extend to like ornaments in series or parallel (preferably using a modular plug like format) thereby creating a string of ornaments suitable for decorating a Christmas tree or the exterior or interior of a home.

[0031] In another embodiment the ornaments linked together are dissimilar and complementary. For example, a string of ornaments may be provided which are formed as described above but which include dissimilar shapes. A string may

include a leaf, a banana, a cherry, a bell, etc. all linked together in a string to provide a pleasing set of lights. In another embodiment, the ornaments may be identical and in one embodiment flashing. In another embodiment the ornaments may be identical but of alternative colours or colour combination or the like, as described  
5 above. Some ornaments may contain more than one light source of different colours which may be alternated for a different effect.

[0032] Any of these sets of ornaments described above may be powered by an AC circuit or by a battery circuit in a conventional power supply, or by wind, solar, or  
10 alternative power.

  
[0033] According to yet another aspect of the invention there may be provided an ornament for the holiday seasons comprising a matrix of clear transparent material such as methylemethacrylate, acrylic, a resin or a Lexan® or the like, wherein said  
15 ornament has at least one light scattering translucent surface, ridge, or channel formed or preferably etched therein or about the perimeter thereof, said ornament including at least one opening containing a lighting source in use (preferably at least one LIGHT SOURCE AND PREFERRED LED), wherein when lit said lighting source will direct incident light within the ornament upon the light scattering  
20 translucent surface, channel or ridge so as to create a more uniform dispersion of light from the ornament as opposed to a point source of light. In a preferred embodiment, the ornaments may be strung together with similar or dissimilar ornaments of alternative shape, colour and design as previously described.

  
[0034] According to yet another aspect of the invention there is provided a sign manufactured from a single sheet of transparent material as described above, said sign having formed and preferably etched therein at least one light scattering design, symbol and/or a message in any language which may be readily identifiable to an observer, said sign including a transparent matrix of methylemethacrylate,

acrylic, resin, Lexan® or the like, or any suitable transparent material of any desired colour or combination of colours which can be etched or alternatively which can have suitable translucent lettering, or design(s), or the like formed therein by, for example, by vacuum forming or alternative molding techniques, said design(s) or message being preferably formed proximate the top of said sign, said edges of said sign having disposed therewith proximate at least one edge thereof openings for at least one light source preferably disposed in or fixed therein and, in one embodiment said openings having contained therein light sources such as light-emitting diodes when the sign is formed, and which are powered by a source of electrical supply through a conductor, in a preferred embodiment said conductor being engaged with the contacts of said lighting source, wherein when the light sources and the preferred light-emitting diodes are powered, incident light strikes said light scattering translucent surface or etching of said message and/or design and highlights the lettering or design to a much greater extent than light emitting from the transparent sections of the display sign. Alternatively, the light sources and preferred light-emitting diodes are not contained within said edge but are disposed within a module including a printed circuit board and the necessary circuitry for powering the light sources and preferred diodes, the tips of said light sources and preferred diodes may be inserted within the openings of said sign or alternatively disposed adjacent thereto in use. The advantages of providing a display sign with the above-mentioned features includes a reduction in power and heat generated for retail signs now requiring neon tubes or other tubes which are made to custom order. The signs of the embodiments of the present inventions therefore may be formed to any desired size and shape and matrix of letters and design, for example each sign providing the shape of a single letter in one embodiment, or alternatively may have the entire message disposed in one sheet, (for example "No Smoking").

0990326 "112301

[0035] In essence therefore, my invention relates to the provision of an etched or otherwise formed translucent light scattering design, lettering, or shape within a matrix contained in the body of a sign or ornament, said sign or ornament having included therewith at least one opening, said opening having contained therewith at least one light source and preferably a light-emitting diode, wherein light emerging from the light-emitting diode incident upon the light scattering translucent design lettering or shape of the sign or the ornament will be enhanced to a much greater extent than any light emanating from the transparent portions of the sign/ornament.

[0036] The invention is not limited by shape, form, colour , or size whatsoever and may take the form by way of example only but not limited to (i) an ornament, for example a Christmas tree string of lights, or individual ornament; (ii) a novelty item, for example a necklace; (iii) a promotional item, for example a display sign for a store window including any alphanumeric character in any language or a internationally recognized symbol or design; (iv) a message, for example an emergency help sign or road marker which may also include any alphanumeric character in any language or a internationally recognized symbol or design; (v) a design, for example a company logo or a clip on personal safety light; (vi) a game, for example a checker or chess board that has sections or playing pieces that illuminate; and (vii) toys of all kinds which may take any possible shape or size in 2 or 3 dimensions.

[0037] The translucent preferably etched light scattering surfaces, ridges, and grooves can be manufactured by injection molding, vacuum forming, die casting, extruding; manual or computerized; routing , drilling, and/or sawing; chemical etching by solution or the like , sandblasting, engraving or any other technique known in the art. A uniform pattern may be provide throughout the design or the pattern may vary from an initial larger spacing gradually decreasing or alternatively increasing. In one example the etching may occur on one side of the sign/ornament only. Alternatively it may occur on two or more sides of the

shape/design. The etching can be very light or aggressively deep , and of various sizes and widths.

5 [0038] Light emitting diodes (LIGHT SOURCE AND PREFERRED LED's) are the preferred light source or their low power consumption performance equivalent which may be powered by A/C current transformed to DC, direct D/C current from a conventional battery source such as disposable batteries or the like, or 12 volt, or solar power or wind power or the like.

10 [0039] The design/sign/ornament described may further comprise in one embodiment LIGHT SOURCE AND PREFERRED LED's of at least one or more colours which in co-operation with a switching device may change the colour of ornament, message or design over time. For example Christmas ornaments may change colour as opposed to or in addition to flashing. In another example an  
15 emergency/road sign may do the same. An audible alarm may also be added.

20 [0040] The LIGHT SOURCE AND PREFERRED LED's may be embedded into the design/sign/ornament when formed, or as an additional step or placed adjacent the surface of the design/sign/ornament when a frame designed to hold the LIGHT SOURCE AND PREFERRED LED's in place is used. Further LIGHT SOURCE AND PREFERRED LED's can also be placed on any angle in/on the design/sign/ornament to maximize the amount of light being scattered internally . The angle can vary to allow the light to disperse for the selected, ornament, sign or design.

25 [0041] Custom coloring may be achieved by tinting the acrylic, Lexan®, or like comparable material prior to manufacturing, for example injection molding to customize various colored designs/signs/ornaments. Further , various light reflecting/scattering media such as mirror like panels, metal flakes or panels such  
30 as chrome, steel, , stainless steel, aluminum or the like can be embedded into the design/ornament/sign or placed on the outer edge, the back the centre or middle



[0042] In another embodiment for a display sign a housing, preferably modular including an opposed rail assembly is provided having inserted therein a preferably substantially concave reflective panel adjacent said sign in order to reflect light and enable use of less LIGHT SOURCE AND PREFERRED LED's while achieving a very satisfactory back light depending on the design/ornament/sign application.

[0044] According to yet another aspect of the invention there is provided a method of manufacturing ornaments/designs or signs from a matrix of clear material such as acrylic, methylmethacrylate, Lexan® or the like, said method comprising:

- (1) identifying a suitable material which may be molded, and when molded having at least one translucent light scattering surface, groove, or ridge;
- (2) placing at least one light source and preferably at least one raw diode in a mold for an ornament/design or sign, said mold structured to provide the final shape of the desired product and locating said light source and preferred raw diodes at positions wherein a light source is desired for the desired product;
- (3) introducing said suitable material into said mold to form the ornament/design or sign in a preferred predetermined shape such as a rectangular or a bell shape, a Santa Claus shape, a cross shape, the shape of a bulb, the shape of a Christmas tree, the shape of fruit, the shape of leaves, the shape of stars, the shape of

circles, or the like; wherein said at least one light source and preferred raw diode is encapsulated in the suitable material when the desired product is molded at the desired positions wherein a light source is desired;

(4) coincidently molding or subsequently forming at least one translucent  
5 preferably etched light scattering surface, groove or ridge within the perimeter of the ornament/design/sign so as to defuse, refract, and otherwise disperse any incident light falling on or near said etched surface, groove or ridge; in one embodiment etching the material adjacent the perimeter of the shape of the ornament proximate at least one location and preferably at a second location, or for  
10 example in the case of a leaf providing the veining outline of a leaf in etched form, or as in the case of Santa Claus providing the facial characteristics with etching or alternatively with fruit providing the etching at the most optimal locations which best simulates the fruit;

(5) preferably providing conductors to engage the at least one light  
15 source for providing power to the sign/ornament/design;

wherein the light incident upon the translucent preferably etched light scattering surfaces, grooves , ridges or characteristics within the sign, design or ornament will scatter, disperse, refract or reflect enhancing the effective lighting and eye appeal of the sign/design/ornament to a much greater extent than any  
20 substantially clear ornament; wherein the at least one light source is molded, encapsulated and fixed within the desired product . In essence therefore when the light source is an LED, and when the desired product is an ornament, the entire ornament formed may be consider as a large light emitting diode. Preferably the electrical connectors may be connected to the light source prior to the molding step  
25 which may involve the manufacture of several ornaments simultaneously . Preferably when the desired product is a display sign the at least one light source may be an array of raw diodes mounted on a circuit board and inserted into the mold prior to the molding step.

09990326-112301

[0045] In one embodiment a display sign may be formed from practicing the method containing a message such as No Smoking, or Fine Dining Here, or Emergency or any such message or advertising that might be displayed to the public so as to obviate the need for neon signs, house numbering, flares, letters or the like. The sign  
5 may be substantially rectangular in shape and may be contained between two display rails which may contain the circuit board which will be disposed adjacent to the edge of the display sign when molded.

[0046] In another embodiment the method is utilized to manufacture ornaments, for  
10 example for Christmas, Halloween or Valentine's Day in many suitable shapes such as in a shape of hearts, Christmas trees, pine cones, pineapples or the like of many different and combinations of colours and variations thereto which are adapted to be connected with a power supply in a modular fashion for example via plug connectors or the like which allows for simple changing of each ornament, for  
15 example the Christmas tree ornaments and their positions in an array.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0047] Figure 1 is a schematic view of an ornament illustrated in a preferred  
20 embodiment of the invention.

[0048] Figure 2 is an alternative embodiment to Figure 1.

[0049] Figure 3 is a schematic illustration of various examples that the ornament  
25 may take illustrated in one embodiment of the invention.

[0050] Figure 4 illustrates a bottom end view of the ornament of Figure 1 illustrated in a preferred embodiment of the invention.

[0051] Figure 5 illustrates a schematic representation of the operation of the ornament of Figure 4 illustrated in a preferred embodiment of the invention.

[0052] Figure 6 is an alternative embodiment to Figure 4.

5

[0053] Figure 7 is an alternative embodiment illustrating universal symbols.

[0054] Figure 8 is an alternative embodiment utilized to replace neon signs and the like illustrated in a preferred embodiment of the invention.

10

[0055] Figure 9 is an alternative embodiment to Figure 1.

[0056] Figure 10 is an illustration of a string of Christmas lights showing various forms of the ornaments and illustrated in an alternative embodiment of the invention.

15

[0057] Figure 11 is an electrical schematic depicting how the invention may be powered in various embodiments.

[0058] Figure 12 is a schematic set of views A, B, C and D which illustrate in one embodiment of the invention the details of the etching of the surface of the ornament which may or may not include a reflective panel.

20

[0059] Figure 13 is a further view of an ornament which might be manufactured according to the teachings of Figure 12 illustrated in one embodiment of the invention.

25

[0060] Figure 14 is a schematic view of a display sign including reflective material therewith shown in one embodiment of the invention.

[0061] Figure 15 is a similar view to that of Figure 14 wherein the design is improved by having a reflective material placed behind the etched surface and illustrated in one embodiment of the invention.

5

[0062] Figure 16A, B and C is a schematic view of one embodiment of the invention having disposed therewith an ornament with more than one light emitting diode and further which may incorporate reflective material.

*Sub 19  
a19*  
[0063] Figure 17 is a schematic view of the assembly of an edge lit sign including modular LIGHT SOURCE AND PREFERRED LEDs for inclusion with said sign and housing for said sign in one embodiment.

[0064] Figure 18 is a schematic view of a method of manufacturing the display sign in one embodiment of the invention.

[0065] Figure 19 is a schematic view of a method of manufacturing ornaments in one aspect of the invention.

**DETAIL LIGHT SOURCE AND PREFERRED LED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

[0066] Referring generally to the figures, there is illustrated an ornament 5 in the various Figures 1, 2, 3, 6, 7 and 9 which includes a transparent matrix of material 10, preferably Lexan®, methylmethacrylate, acrylic or the like, of any colour or combination thereof, which has therein disposed an translucent light scattering etched surface 15 which may be etched using robotic methods to form a groove having side portions extending to a predetermined depth d as best seen in Figure 4. The groove and the wall surrounding the groove therefore are etched to become

15

20

25

Sub  
a2<sup>25</sup>

5

10

15

25

20

[0072] Referring now to Figure 11, there is illustrated an block diagram showing the various alternative power supplies for powering a set of ornaments, a sign, or more than one sign or various displays embodying the invention.. The power may come from those sources already known in the art including alternating current from a power supply such as a wind turbine, a solar panel, a portable generator, or from line current depending on the location of the installation of the sign or ornament set being used. For example it would be appropriate in an emergency situation to utilize a generator if it is desired that an alternating current be used with the emergency sign for example, "Road Closed" or "Traffic Incident Ahead" or the like. In a more permanent situation a solar panel would be more suitable or alternatively a connection to a household current may be practical. Finally, for some situations for example, emergency signs utilized when a car is broken down, a battery current source may be more appropriate for example via a connector to a cigarette lighter type port for access to the 12 volt circuit of a car. A battery may be used as a back-up source of power for typical situations. Those skill in the art will appreciate all the permutations and combinations possible. It may be necessary to gate the current if flashing is desired or provide some alternative type of switching if the sign or ornament or display includes more than one coloured light emitting diode. In this matter, for example a Christmas ornament may light in one colour for a set period of time and then may be switched to light a second LIGHT SOURCE AND PREFERRED LED under the control of an inexpensive controller to change the colours displayed then perhaps alternatively flash depending on the sophistication of the sign. For example, when the invention is utilized for a sign for advertising purposes for a business to replace neon signs or the like, it may be advantageous to have each letter light separately so that they may flash in sequence or in unison to draw the public's attention to the sign. Many other configurations are possible as would be apparent to those skill in the art when reading this entire specification. No limitation is intended whatsoever.

Sub  
222

09990326-112301



5

15

25

the sign or when the sign is manufactured by the techniques described above. Alternatively, the sign 60 and lettering 61 may be enhanced for viewing by the public by providing a reflective material behind the sign to further enhance the dispersion of light within the said sign and to minimize dark spots.

5

[0076] Figure 15 also provides an embodiment of display 10 illustrating a etched rabbit 15x having a translucent surface or outline and when light from said LIGHT SOURCE AND PREFERRED LED 20 strikes the etched surface 15x, a pleasing effect is achieved which may further be enhanced by the reflective material 10a outlining the shape of the rabbit which is be placed behind the etched surface of the rabbit of the design 10 to minimize dark spots and provide a more efficient ornament.

10

15

20

25

[0077] In another embodiment as shown best in Figure 16 light emitting diodes 71a and 71b are provided at each end of the ornament 70 made from acrylic 70a which includes flecks of metal 74 disposed within the acrylic material when the ornament 70 is formed. The LIGHT SOURCE AND PREFERRED LED's 71a and 71b will provide red light 73 therefrom or amber light 72 therefrom respectively which LIGHT SOURCE AND PREFERRED LED's may be light simultaneously to be melded together, or alternatively used or flashed or switched so that the ornament 70 may express various combinations of effects. These effects are also meant in this specification for all embodiment of the invention and not in a limiting sense. Reflective flecks 74 disposed within said ornament creates a further dispersion of the light which will be further dispersed by the translucent surfaces on the surface of the ornament as best seen in relation to Figure 13 to thereby minimize dark spots. The ornament therefore would include both the etched surface not shown in Figure 16 and the reflective flecks contained therein at 74 to improve the lighting characteristics of the ornament and obtaining a much more effective ornament in spite of the use of the low power consumption LIGHT SOURCE AND PREFERRED LEDs. In addition as shown in Figure 16B reflective material may be placed on the

094326-11301

outer edge of the circular shaped embodiments of the ornament 70. In another embodiment in Figure 16C the ornament 80 includes two halves 82 and 81 wherein compatibly shaped reflective material 83 is contained there between wherein the image I which includes an etched or translucent surface is further enhanced by the reflective material which may be on both sides of material 83. Further an image I may be included on both halves 81 and 82 of the ornament 80.

[0078] Referring now to Figure 17 there is illustrated a modular housing 90 which includes rail portions 91 and 92 provided at the bottom and at the top of the housing wherein LIGHT SOURCE AND PREFERRED LED circuit boards 94 including LIGHT SOURCE AND PREFERRED LED's 92a may be disposed within either the top or bottom or both the top and bottom rails 91 and 92. The board 94 is inserted into the space 90b with the side edges thereof resting on flanges 90a so that the circuit board directs the LIGHT SOURCE AND PREFERRED LED's proximate the edge 61 of the acrylic panel 60. The panel 60, as shown previously, may include an image or an alphanumeric set of characters in any language providing an emergency sign for example. The edges 61 at the top and bottom are to be light by the array of LIGHT SOURCE AND PREFERRED LED's on the printed circuit board 94 disposed within the rail 91 and 92 in space 90b.

[0079] Alternatively, openings may be provided in the panel 60 proximate the edges 61 as seen in Figure 8 to receive the LIGHT SOURCE AND PREFERRED LED's on the printed circuit board prior to being inserted within the rail 91 and 92. In a preferred embodiment a mirror like reflective panel (whether corrugated or flat) and preferably a concave panel 60' may be provided that fits into the housing 90 as well to further enhance the light emanating from the panel as previously described and the effectiveness and efficiency of the panel when viewed by a member of the public.

EXAMPLES OF USES FOR THE INVENTION (All examples are to include a primary etched pattern, figure, message or the like with or without secondary light reflectors or flecks)

5 **[0080] For Garden and Landscaping Applications**

1. Patio stones with built in light
2. Outside lighted steps
3. Lighted walkways
4. Lighted deck steps, posts and stairways
5. Lighted railings and banisters
6. Lighted welcome signs
7. Lighted decorative water fountains for indoor and outdoor
8. Lighted waterfalls
9. Lighted birdbaths
10. Swimming pool accent lighting
11. Lighted driveways and curbs
12. Lighted decorative rock lighting

**[0081] For Exterior Building Applications**

- |    |    |                                               |
|----|----|-----------------------------------------------|
| 20 | 1. | Accent lighting for high-rise buildings       |
|    | 2. | Lighted address numbers                       |
|    | 3. | Lighted signs for advertising and directional |
|    | 4. | Decorative lighting for building exteriors    |
|    | 5. | Lighted perimeter flashing trim elements      |
| 25 | 6. | Accent lighting for doors, windows and frames |

**[0082] For Indoor Accent Lighting Applications**

1. Lighted baseboards and nightlights

- 10 [0083] For Road Signs and Markers

- 20 [0084] Figure 18 is a schematic view of the method of manufacturing a display sign wherein a circuit board (94) having raw diodes (92x) attached thereto in series separated by a distance equivalent to the separation of the distance of mold openings (M<sub>a</sub>) within mould (M<sub>1</sub>). The mould has two halves wherein when separated the raw diodes (92<sub>x</sub>) attached to circuit board (94) are inserted therein
- 25 prior to inserting moulding material, typically acrylic, within the mould in a manner well-known in the art. When completed therefore the raw diodes are coated and sealed via the acrylic material integrating within the display sign. Therefore, LED's are not required in manufacturing the display sign in this aspect of the invention, utilizing the method thereof. The raw diodes may be purchased and assembled on

the circuit board (94) spaced as shown as indicated consistent with the spacings in the mould of the openings ( $M_a$ ). Raw diodes are less expensive than light emitting diodes and the resultant display sign would therefore have these raw diodes encapsulated in the openings thereof. It is also contemplated using the same method in relation to manufacturing ornaments.

[0085] Referring to Figure 19 there is illustrated a mould ( $M_2$ ) having openings ( $M_b$ ) therein, each having the shape of a desired three dimensional ornament, such as the ornaments A, P, T and D as shown. The mould ( $M_2$ ) includes two halves which may be separated with the raw diode being inserted separately into each of the openings for each particular desired ornament. The mould is then closed and the desired material, for example acrylic whether transparent or colored, may be pumped into the mould with the raw diodes being encapsulated by that material. When the moulds are opened the contacts shown in the figures connected to the raw diodes are then available for connection to known connecting sockets, etc. for arrays of lights.

[0086] The methods illustrated in figure 18 and 19 are for the manufacturing of signs and ornaments moulded from a matrix of clear material such as acrylic, methylemethacrylate, Lexan® or the like.

[0087] The method includes the steps of:

(1) Identifying a suitable material to be used for molding the sign or ornament, and while molded also forming the translucent light scattering surface, groove, ridge or characteristic into the sign or ornament.

(2) Placing the raw diodes in a mold at the positions indicated in Figures 18 and 19 for the sign or ornament, wherein the internal surface of the mold is structured to form the final shape and characteristics of the desired product.

5

10

15

20

25

as previously described with the circuit board disposed adjacent to the edge of the display sign when molded.

[0090] The method is also utilized to manufacture ornaments, for example for  
5 Christmas, Halloween or Valentine's Day in many suitable shapes such as in a shape  
of hearts, Christmas trees, pine cones, pineapples or the like of many different and  
combinations of colours and variations thereto which are adapted to be connected to  
the power supply in a modular fashion for example via plug connectors or the like  
which allows for simple changing of each ornament, for example the Christmas tree  
10 ornaments and their positions in an array.

[0091] The above listing of uses is not intended to be limiting in any way. Many  
changes can be made to the invention without departing from the scope thereof. It is  
intended that all material contained herein be interpreted as illustrative of the  
15 invention and not in a limiting sense.

TOE2T"92E0660